

“SUHBA Safe Contractor”

SUHBA’s goal is to raise awareness and safety culture with contractors.



Make safety your top priority - putting safety first can help reduce costs and improve productivity on the jobsite.

Hold everyone accountable – everyone who sets foot on the jobsite is responsible for safety.

How to qualify – email this completed form to kris@suhba.com to qualify as a “SUHBA Safe Contractor”. We will promote safe builders and contractors in the Parade Magazine, Building Guide, SUHBA website, social media, SUHBA newsletter, and a promotional sign at SUBHA events.

-
- REPORTING:** All accidents and injuries must be immediately reported to the Project Manager.
 - INDEMNITY FOR SAFETY VIOLATIONS:** Subcontractor shall conform to the Occupational Safety Health Act of 1970, the Contraction Safety Act of 1969 and all standards and regulations which have been or shall be promulgated by the parties or agencies which administer said Acts, as well as all applicable state or local occupational health and safety ordinances. Subcontractor shall directly receive and respond to, defend and be responsible for any citation, order, claim, charge, or criminal or civil actions, arising by reason of the failure of Subcontractor or its agents, employees, supplies, and subcontractors to so comply, regardless of whether such non-compliance results from active or passive acts or matters against which Subcontractor is obligated hereunder to indemnify & hold harmless the Owner, Project Manager, & General Contractor from & against any liability, loss, damage, costs, claims, awards, judgments, fines, expenses, including litigation expenses, reasonable attorney’s fees, claims or liability for harm to persons or property. (if applicable)
 - LADDERS:** The extension ladder must extend 3' above the entry point of the trench, floor, or roof and tied off. Workers are never to use a stepladder as a single ladder that is leaning against a wall while in the closed position. Workers are never to stand on the top step of a stepladder, or where the midline of their body extends past side of the ladder. Any ladder that is damaged must be tagged "Out of Service" and be removed from the job site. Job-built ladders are not permitted.
 - POWER TOOLS & CORDS:** Cut or frayed extension cords must never be used and must be tagged "Out of Service" and be removed from the job site. Damaged tools must be tagged "Out of Service" and be removed from the job site.
 - FIRE PREVENTION:** "Smoking" is not permitted in homes under construction at any time. Gasoline and other flammable liquids are not permitted in any house.

- FRAMERS:** 42" Safety railings with toe boards will be installed at any openings and/or elevated platform greater than 6' in fall height/depth. (if applicable)
- ROOFERS:** An approved personal fall arrest system including a safety harness is required when working on a roof greater than 6' from the ground. (if applicable)
- STUCCO:** 42" Safety railings with toe boards will be installed and tied off to the house for scaffolding greater than 6' in height. (if applicable)
- DRYWALL:** Metal scaffolding shall be used for high ceilings and stairways instead of job-built scaffolding. (if applicable)
- PAINTERS:** Respirator is to be worn when spraying. (if applicable)
- COMPETENT SUPERVISION:** Each Subcontractor is required to have a competent person that always speaks English on site. A competent person is one that can identify safety hazards and has the authority to stop work until known hazards have been eliminated before proceeding.
- SUBMIT PICTURES:** Self-certify by submitting pictures to kris@suhba.com.
- LOGO:** Email your logo to kris@suhba.com.

By completing and signing this form you are agreeing that the above items are being implemented on your jobsites.

Contractor (Print Name)

Contractor Signature

Date